

FRAC-PIPE™

HANDY PIPE™

Sizes: 1" O.D. (25 mm) to 2.37" O.D. (60 mm)

FLATWATER FLEET®

www.flatwaterfleet.com

INC.



FRAC-PIPE™ is constructed of rustproof stainless steel providing a very high life span resulting in very low recurrent costs.



- Patented, hand-tightened joint provides fast and easy installation or removal.
- 1½" (38 mm) size handles pressure in excess of 4,000 psi (280 bar.) and pulls in excess of 7 tons.
- Lightweight, thin-wall design reduces hauling costs - eliminates need for hoisting derrick. Simplifies handling and storage.
- Only 2½ turns fully tightens joint - O-Ring seal.
- Standard lengths of 5' (1.5 m), 10' (3.0 m) and 20' (6.0 m) – custom lengths available.
- Rigid and durable – not affected by cold temperatures.
- Field proven.
- Versatile. Several uses from a single investment.

**For those who want get ahead
...not just get by**

LIGHTWEIGHT STAINLESS STEEL FRAC-PIPE™

Flatwater Fleet's lightweight stainless steel FRAC-PIPE™ replaces heavier, longer, cumbersome pipe that was used in the past. The larger size range makes FRAC-PIPE™ ideal for many water well applications.

USES INCLUDE

- Hydrofracturing
- Grouting
- Air-Lift Pumping
- H.P. Jet Cleaning
- Acidizing
- Pump Risers
- Environmental well casing



- Complete line of adapters available for all sizes and applications.



Hand tightened joint!

Specifications on reverse side.

SPECIFICATIONS

STANDARD RANGE

Type	Outer Diameter	Wall Thickness	Weight	Main Use
SP-22A2	9/16" (14.3mm)	.04" (1.0mm)	0.1 lbs./ft. (0.05 kg/m)	Jetting, pump riser, airlift pumping
SP-22A3	1.0" (25.0mm)	.04" (1.0mm)	0.4 lbs./ft. (0.6 kg/m)	Grouting, jetting, pump riser, airlift pumping
SP-22A1*	1.5" (38.0mm)	.06" (1.5mm)	0.9 lbs./ft. (1.37 kg/m)	Hydrofracturing, grouting, jetting, airlift pumping
SP-22A4	2.37" (60.3mm)	.06" (1.5mm)	1.5 lbs./ft. (2.21 kg/m)	Well casing, airlift pumping, grouting

Length: Standard length is 5 ft.(1.5m), 10 ft.(3.0m) or 20 ft.(6.0m). Other lengths are available on request.

Adapters: For connections of FRAC-PIPE™ systems to conventional NPT or BSPT type of threads are standard. Other adapters are available on request.

Availability: 1.0" and 1.5" O.D. pipe in 5 ft., 10 ft. and 20 ft. lengths are stock.

* **Burst Pressure:** 4,000 psi (280 bar)

Pull Apart Force: 14,000 lbs. (6,350 kg)



Flatwater Fleet, Inc., reserves the right to change specifications at any time without notice as part of our goal to constantly seek product improvements. The only warranty applicable is our standard written warranty. No other warranties exist whether expressed or implied.

**FLATWATER®
FLEET**
INC.

5354 Twig Blvd. • Saginaw (Duluth), MN 55779 USA
Phone: 218/729-8721 • FAX: 218/729-7644

WAF5-97/REV CE6-02